




Doors can be opened and bin removed without lifting the lid. The lid is hinged & have gas struts to assist with lifting, allowing access to the bins in situ.

BIN STORE	FOOTPRINT		LID		HEIGHT		INTERNAL			DOOR CLEARANCE	
(mm)	WIDTH	DEPTH	WIDTH	DEPTH	FRONT	BACK	BIN ACCESS HEIGHT	WIDTH	DEPTH	STD DOORS	BIFOLD DOORS
UNO	750	1000	870	1120	1275	1340	1090	650	900	650	-
DUO	1350	1000	1470	1120	1275	1340	1090	1250	900	640	-
TRIO	2000	1000	2120	1120	1275	1340	1090	1900	900	965	475

All timber is UK Grown Kiln Dried Douglas Fir.
Exterior High Grade Plywood Floor (Painted), Shelf & Roof.
Tough, Flexible EPDM Rubber Roof Membrane

Hardware included in all Roll-in Models:

- Adjustable Metal Feet
- Gas Strut Stays
- Stainless Steel Hinges
- Strong Door Drop Bolts
- Black Medal Handles & Thumb Turn

SOLID BASE REQUIRED			TYPES OF BASE:
	WIDTH	DEPTH	
UNO	850	1100	• Concrete Pad • Eco Grid & Shingle • Paving Slabs/Brick • Tarmac/Resin Bound Surfacing Unsuitable Bases include soil or loose shingle - anything that is not compact & solid.
DUO	1450	1100	
TRIO	2100	1100	