



Doors can be opened and bin removed without lifting the lid. The lid is hinged & have gas struts to assist with lifting, allowing access to the bins in situ.

| BIN STORE | FOOTPRINT |       | LID   |       | HEIGHT |      | INTERNAL          |       |       | DOOR CLEARANCE |              |
|-----------|-----------|-------|-------|-------|--------|------|-------------------|-------|-------|----------------|--------------|
|           | WIDTH     | DEPTH | WIDTH | DEPTH | FRONT  | BACK | BIN ACCESS HEIGHT | WIDTH | DEPTH | STD DOORS      | BIFOLD DOORS |
| UNO       | 750       | 1000  | 870   | 1120  | 1275   | 1340 | 1090              | 650   | 915   | 650            | -            |
| DUO       | 1350      | 1000  | 1470  | 1120  | 1275   | 1340 | 1090              | 1250  | 915   | 640            | -            |
| TRIO      | 2000      | 1000  | 2120  | 1120  | 1275   | 1340 | 1090              | 1900  | 915   | 965            | 475          |

All timber is UK Grown Kiln Dried Douglas Fir.  
Exterior High Grade Plywood Floor (Painted), Shelf & Roof.  
Tough, Flexible EPDM Rubber Roof Membrane

Hardware included in all Roll-in Models:

- Adjustable Metal Feet
- Gas Strut Stays
- Stainless Steel Hinges
- Strong Door Drop Bolts
- Black Medal Handles & Thumb Turn

| SOLID BASE REQUIRED |       |       | TYPES OF BASE:  |
|---------------------|-------|-------|---|
|                     | WIDTH | DEPTH |   |
| UNO                 | 850   | 1100  | <ul style="list-style-type: none"> <li>• Concrete Pad</li> <li>• Eco Grid &amp; Shingle</li> <li>• Paving Slabs/Brick</li> <li>• Tarmac/Resin Bound Surfacing</li> </ul> Unsuitable Bases include soil or loose shingle - anything that is not compact & solid. |
| DUO                 | 1450  | 1100  |   |
| TRIO                | 2100  | 1100  |   |