



ROLL-IN RANGE



ROLL-IN	FOOTPRINT		LID		HEIGHT			INTERNAL			DOOR CLEARANCE	
	WIDTH	DEPTH	WIDTH	DEPTH	BACK	FRONT	PEAK	HEIGHT	WIDTH	DEPTH	STD DOORS	BIFOLD DOORS
3	1500	2100	1620	2245	1200	1275	1330	1140	1400	2000	715	-
4	1800	2100	1920	2245	1200	1275	1330	1140	1700	2000	865	425
5	2100	2100	2220	2245	1200	1275	1330	1140	2000	2000	1015	500
6	2400	2100	2520	2245	1200	1275	1330	1140	2300	2000	-	575

All timber is UK Grown Kiln Dried Douglas Fir.
 Exterior High Grade Plywood Floor (Painted), Shelf & Roof.
 Tough, Flexible EPDM Rubber Roof Membrane

Hardware included in all Roll-in Models:

- Adjustable Metal Feet
- Gas Strut Stays
- Stainless Steel Hinges
- Strong Door Drop Bolts
- Heavy Duty Hasp & Staple
- Anti-Tampering Plate
- Round Shackleless Padlock

SOLID BASE REQUIRED			TYPES OF BASE:
ROLL-IN	WIDTH	DEPTH	
3	1600	2200	<ul style="list-style-type: none"> • Concrete Pad • Eco Grid & Shingle • Paving Slabs/Brick • Tarmac/Resin Bound Surfacing Unsuitable Bases include soil or loose shingle - anything that is not compact & solid.
4	1900	2200	
5	2200	2200	
6	2500	2200	